

ACT

ACOUSTIC TAPE

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Excellent noise reduction properties
- > Soft and flexible
- > Rotting resistant

TYPICAL APPLICATIONS

- > Ideal for general building applications
- > Primarily used for acoustic insulation when installing partition walls
- > The material provides secure sealing between construction parts and walls, floor etc

CONSTRUCTION

Backing: Foam PE

Adhesive: Acrylic

COLOR(S)



Anthracite

STANDARD SIZE

Width(s): 30mm, 50mm, 75mm, 95mm

Length(s): 30m

Contact your BDT sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	3	mm	± 0,35
Foam density	25	kg/m ³	± 3
Elongation	110	%	± 30
Service Temperature Range	to +100	° C	-
	to +212	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and preformed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (5°C - 30°C (41°F - 86°F) and <70% relative humidity) away from direct sunlight and should be used within 6 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

