



Corrugated Pipe Connector

Material: polyethylene (PE)


Temp: polyethylene (PE)-40°C~+80°C

Colour: Black , other color as request

Properties: Reasonable tubing assembly due to one-piece screw connector with push-in lock, simple dismounting by pressing the snap-in sleeve; under narrow working conditions, please select the connector and hose with a smaller outer diameter; the connector can effectively prevent the entry of oil; acid solvents and dust.

Application: For protectively insulated electrical installations;

Protection rate: IP65



Thread	Applicable tubing Outer ϕ	Length of thread C(mm)	Smallest inner ϕI (mm)	Largest outer ϕB (mm)	Total Length (mm)
CGBAD10-100	10	12	6.5	17	34.5
CGBAD13-100	13	12	7	20	37
CGBAD15.8-100	15.8	12	11.5	23	39
CGBAD21.2-100	21.2	13	15.5	29.5	44.5
CGBAD25 -100	25	13	20.5	34	46.5
CGBAD28.5-100	28.5	13	23.5	37	47

On1Shelf® is Trademark of Digital Isle Limited
Unit 15, Cowan's Yard
39 Newtown Road, Camlough, BT35 7JJ
Tel: 02830278150 Fax: 02830278150
E-mail: sales@on1shelf.com